

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione


Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it



Technical Datasheet

tasker® TSK74 – 2x1,50 mm²

Siliconic Flat Audio Divisible Cable for High Temperature



CATEGORY Flat Divisible Audio Cable
APPLICATIONS Medical, water park, beauty center, harsh environment and temperature

A: Extra Soft White Silicon Rubber sheath.
Outer cable dimension 2,80x5,60 (±0,20) mm.

B: Both conductors in O.F.C. Tinned Copper.
Stranded formation 30x0,25 mm.
Nominal cross section 2x1,50 mm².

MARKING tasker® TSK74 - 2x1,50 mm² - O.F.C. – Siliconic Audio Cable - Temp. Range - 60/+180°C – Made In Italy

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PVC or PUR.

Conductors Properties

Conductor Resistance	13,70 Ω/Km
Max Rated Voltage U₀/U	300/500 V
Min. Bending Radius	4xouter Ø
Operative Temperature	-60/+180°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
	X	Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			