

EP22A-B Digital Podium

Basic presentations that require multiple additional devices, communication and power ports, Switch & Scalar panel, EP22A-B. Professional and more technical meetings, conferences and classes are the places for EP22A-B. Well designed, dedicated work-areas on top surface allows the speaker to make the presentation neat and tidy.

EP22A-B

- 22" Multi touch capacitive touch screen
- Switch & Scalar
- Built in high performance PC.
- Professional microphones
- Superior materials, firm and durable
- Multiple color options



Wide touch screen designed with IPS technology. Multiple types of connectors for complex purpose and controls. Steady work place for documents and additional devices.



Slim design, appropriate standing position



Well balanced, durable, wide body



Multiple connectors to connect existing devices at the hall. Protection cover.

EP22A-B Technical Specifications

Main Specifications	
Speaker Screen	22" Full HD Multi Touch Capacitive Touch Screen
Built-in PC for Speaker Screen	intel i3 4GB Ram, 120 SSD, Win 10 Embedded IoT
Switch	Atlona SC-500 3x1 switcher with two HDMI inputs and one VGA input
Scaler	HD video scaler with HDMI output and input resolution control
Source selection	Automatic input selection and automatic display control
Amplifier	
Mixer	
Microphone	1 pcs 18" Shure Gooseneck Condenser Microphone

Lecturer Panel	
Resolution	1920x1080 FHD
Brightness	250 cd/m2
Aspect ratio	16:9
Touch Screen Technology	Capacitive
Touch Points	10 points

Lecturer Panel PC Specifications	
CPU	4th Generation Intel Core i3
RAM	4 GB DDR4
HDD	120 GB SSD
Operating System	Windows Embedded 10 IoT

Microphone	
Length	18"
No of microphone	2 pcs
Output Connector	3-way XLR (Male)
Microphone Type	Cardioid
Frequency Response	50 -18 kHz
Sensitivity (at 1,000Hz)	-60dB ± 3dB
Impedance	220Ω
Power ON indicator	LED
Power requirement	2xPhantom Power (48V)

Inputs (on Speaker Panel)	
Sound	Available (On desk for laptop)
HDMI	3,5mm jak (On desk for laptop)
Ethernet	Available (On desk for laptop)
230V Plus (Max 5A)	Available (On desk for laptop/mobile phone charge)
USB	USB 2.0 x 4 (On desk for internal PC)

Outputs (Bottom of Podium)	
HDMI	Available (Protector Out) (max output 1080p)
RS232	For projector On/Off

Data Connection (Bottom of Podium)	
Ethernet 1	Network Connection for Complete System

Power	
Power Input	230V 50Hz
Power Consumption	550W (max)

Peripherals & other features	
Color	Grey (RAL 7047)
Packing	Wooden box export packing

Mechanical Specs	
Outline Dimension (mm)	Set: 580 x 1160 x 980 Package: 676 x 1256 x 1186
Weight (kg)	Set: 76 kg Package: 117 kg
Optional features	Flight case

EP22A-B Mechanical Specifications

