

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

# tasker® C114 – 2x0,25 mm<sup>2</sup> Even in White

### Low Capacity Balanced Microphone Cable



A	B	C	D	E
---	---	---	---	---

**CATEGORY**  
**APPLICATIONS**

Balanced Microphone Cable (See Audio Catalogue)  
 Pre Made Audio Cables and Microphones.

- A:** Soft **PVC** Sheath – Available in different color .  
Outer cable Diam. Ø 6,00 (±0,20) mm.
- B:** Shielding O.F.C. red copper Spiral covering 100%.
- C:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Core Insulation with a compact PE, colored one Orange and one Transparent. Diam. Ø 1,50 (±0,20) mm.
- E:** O.F.C. red copper, formation 8x0,20 mm.  
Nom. Cross section 2x0,25 mm<sup>2</sup>.

**MARKING**

**tasker® C 114 2x0.25 – 23 AWG O.F.C. Low Capacitance Flex Microphone Cable**  
 Made in Italy

**AVAILABLE ALSO**  
**CUSTOM**  
**PRODUCTION**

C114 LSZH, C114 PE  
 This product may be custom produced also in **PUR**, and in all other versions with Metallic Armor.

**Cable Properties**

<b>Conductor Resistance</b>	75 Ω/Km
<b>Capacity Core/Core</b>	55 pF/mt
<b>Capacity Core/Shield</b>	90 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			