

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C124 - 2x0,12 mm² - Shielded Flat Audio Cable



A	B	C	D
---	---	---	---

CATEGORY Shielded Flat Audio Cables (See Audio Catalogue)
APPLICATIONS Audio Premade Cable and head-phones

- A:** Black Soft PVC sheath.
Outer cable Dimensions: 2,40x5,00 (±0,10) mm.
- B:** The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with PVC, colored one White and one Red.
Diam. Ø 1,10 (±0,10) mm.
- D:** O.F.C. red copper formation 16x0,10 mm
Nom. Cross section 2x0,12 mm².

MARKING tasker® C 124 2x0,12 mm² O.F.C. Shielded Flat Cable
CUSTOM PRODUCTION This product may be custom produced also in LSZH polymer, PE, or PUR.

Cable Properties

Conductor Resistance	140 Ω/Km
Capacity Core/Core	70 pF/mt
Capacity Core/Shield	340 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			