DL27M Digital Podium

The DL27M is specially designed podium, adjustable to various heights according to the needs the speaker. The 27" high precision touch screen allow the speaker to take notes and interact with the presentation more convenietly.

Connecting your projector and sound system to the DL27M is as easy as connecting the cables.



DL27M Technical Specifications

Main Specifications	
Lecturer Screen	27" Multi touch capacitive
Front Screen	
Built-in PC for Speaker Screen	intel i3 4GB Ram, 120 SSD, Win 10 Embedded ioT
Microphone	1 pcs 18" Gooseneck Condenser Microphone
Lifting Column	Available

Lecturer Panel	27"
Screen Specifications Resolution	1920x1080 FHD
Brightness	250 cd/m2
Aspect ratio	16:9
Touch Screen Technology Touch Points	Capacitive
Lecturer Panel PC Specifications	10 points
CPU	4th Generation Intel Core i3
RAM	4 GB DDR4
HDD	120 GB SSD
Operating System	Windows Embedded 10 IoT

Microphone	
Length	18"
No of microphone	2 pcs
Output Connector	3-way XLR (Male)
Microphone Type	Cardioid
Frequency Response	50 -18 kHz
Sensitivity (at 1,000Hz)	-60dB ± 3dB
Impedance	220Ω
Power ON indicator	LED
Power requirement	2xPhantom Power (48V)

Inputs (on Speaker Panel)	
USB	USB 2.0 X 4 (for internal PC)
Height adjusment	up&down

Outputs (Bottom of Podium)	100
HDMI	Available
Ethernet	Available
XLR for microphone	Available
USB	USB 2.0 x 2 (for internal PC)

Height Adjust Engine	The state of the s
Movement	Vertical (Up/Down)
Control	By Buttons (Up/Down)
Speed	Max speed: 38 mm/s
Lifting strength	700N
Locking System	Automatic Looking when engine not working
Engine Type	Electrical

Power	
Power Input	230V 50Hz
Power Consumption	400W (max)

Grey (RAL 7047)

Wooden box export packing

lechanical Specs	
Minimum Height	783 mm
Maximum Height	1233 mm
Outline Dimension (mm)	Set: 526 x 798 x 783 Package : 622 x 894 x 989
Weight (kg)	Set: 63 kg Package : 108 kg
Optional features	Flight case



Peripherals & other features

Color

Packing





