

# ML22T Digital Podium

ML22T covers your professional presentation requirements and complex needs with its complete solutions. Sliding top panel both protects your touch display and becomes a platform for your documents, laptop. Multi-purpose complete connector panels give ability to access to power, external projector and display devices, and audio systems from professional control panel. Speakers can convey their voice through advanced microphone more precisely. Additional holes on the platform are suitable for placing tablets and accessories. ML22T strengthens presentations, lectures as to be suitable for advanced conference rooms.

## ML22T

- 22" Multi touch capacitive touch screen
- Switch & Scalar
- Professional microphones
- Superior materials, firm and durable
- Multiple color options
- Built in high performance PC.



Sliding top platform both protects built-in display, controls and becomes surface for additional laptop and documents. The wide, touch display is designed with IPS Technology to prevent picture loss during angle change. Additional holes for tablets and accessories. Multi-purpose advanced power, audio visual connectors.



Durable and easily movable body with multiple color options.



Hidden external connectors for installed cables in the hall.



Built-in high performance PC. Wide maintenance and working space

Main Specifications	
Speaker Screen	22" Full HD Multi Touch Capacitive Touch Screen
Built-in PC for Speaker Screen	intel i3 4GB Ram, 120 SSD, Win 10 Embedded IoT
Switch	Atlona SC-500 3x1 switcher with two HDMI inputs and one VGA input
Scaler	HD video scaler with HDMI output and input resolution control
Source selection	Automatic input selection and automatic display control
Sliding cover	Available for top podium with lock
Microphone	1 pcs 18" Shure Gooseneck Condenser Microphone

Lecturer Panel	
Resolution	22"
Brightness	1920x1080 FHD
Aspect ratio	250 cd/m2
Touch Screen Technology	16:9
Touch Points	Capacitive
	10 points

Lecturer Panel PC Specifications	
CPU	4th Generation Intel Core i3
RAM	4 GB DDR4
HDD	120 GB SSD
Operating System	Windows Embedded 10 IoT

Microphone	
Length	18"
No of microphone	2 pcs
Output Connector	3-way XLR (Male)
Microphone Type	Cardioid
Frequency Response	50 -18 kHz
Sensitivity (at 1,000Hz)	-60dB ± 3dB
Impedance	220Ω
Power ON indicator	LED
Power requirement	2xPhantom Power (48V)

Inputs (on Speaker Panel)	
HDMI	Available (On desk for laptop)
Sound	3.5mm jak (On desk for laptop)
Ethernet	Available (On desk for laptop)
230V Plus (Max 5A)	Available (On desk for laptop/mobile phone charge)
USB	USB 2.0 x 4 (On desk for internal PC)

Outputs (Bottom of Podium)	
HDMI	Available (Protector Out) (max output 1080p)
RS232	For projector On/Off

Data Connection (Bottom of Podium)	
Ethernet 1	Network Connection for Complete System

Power	
Power Input	230V 50Hz
Power Consumption	550W (max)

Peripherals & other features	
Color	Grey (RAL 7047)
Services door	Two sided servis door
Drawer	Available
Packing	Wooden box export packing

Mechanical Specs	
Outline Dimension (mm)	Set: 754 x 810 x 1049 Package: 890 x 906 x 1255
Weight (kg)	Set: 104 kg Package: 161 kg
Optional features	Flight case

