

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet



# tasker® C118 - 2x0,14 mm<sup>2</sup> - Shielded Flat Audio Cable



A	B	C	D
---	---	---	---

**CATEGORY** Shielded Flat Audio Cables (See Audio Catalogue)  
**APPLICATIONS** Audio Premade Cable and head-phones.

- A:** Soft **PVC** Sheath – Available in different colors.  
Outer cable Dimensions: 2,90x5,80 (±0,10) mm.
- B:** The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with PVC, colored one Red and one Yellow.  
Diam. Ø: 1,40 (±0,10) mm.
- D:** O.F.C. red copper formation 18x0,10 mm.  
Nom. Cross section 2x0,14 mm<sup>2</sup>.

**MARKING** tasker® C118 2x0,14 mm<sup>2</sup> O.F.C. Shielded Flat Cable  
**CUSTOM PRODUCTION** This product may be custom produced also in **LSZH** polymer, **PE** or **PUR**.

### Cable Properties

<b>Conductor Resistance</b>	138 Ω/Km
<b>Capacity Core/Core</b>	65 pF/mt
<b>Capacity Core/Shield</b>	280 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			